

Technical Data Sheet

Preliminary



Shieldex® CombiTex

No.: 110040113

Purpose	Conductive fabric for general use
Description	Double sided knitted fabric Black side non-conductive PES Silver plated side conductive PA
Raw Material	63 % PES, 37 % PA
Surface Resistivity	$< 1 \Omega/\square$
Temperature Range / Storage / Handling	-30 °C to 90 °C According to our care and handling instructions
Total Thickness	1,05 mm \pm 10 %
Weight	234 g/m ² \pm 10 %
Roll Width	130 cm / \pm 5 cm
Roll Length	Average 30 m

Compliance and Certification

DIN EN ISO 9001:2015

REACH

RoHS

Produktions- und Vertriebs GmbH

Kleiner Ort 11 - 28357 Bremen - Germany

☎: +49 421 27 50 47 - 📠: +49 421 27 36 43

info@statex.de - www.statex.de

The above information has been compiled from our manufacturer area according to the latest state of development and application technology. Since application and further processing are beyond our control, no liability of the producer can be derived from the contents of the data sheet. All deviant or transcending data sheet information must be confirmed in written form by the manufacturer. Our general terms and conditions apply in all cases. All previous data sheets are invalid with the publication of this data sheet. Please note as well our handling and storage instructions accessible at www.statex.de.

Alterations Reserved 24.05.2017/01